

Honda Generator ECT 7000P

Four-stroke reliability housed within the traditional generator frame appliances. 6,5 litre fuel tank running on unleaded petrol. This model will provide 7000 watts of power for 2.6 hours before requiring a re-fill. Oil Alert prevents engine damage by automatically shutting the unit down if the oil drops below a safe operating level.

Durable frame of high quality welded and powder coated durable steel frame for extended durability, easy lifting and light weight. Rubber engine mounts greatly reduce operating noise and vibration whilst maximising frame life. Circuit breaker outlets avoid equipment damage and injury in the event of a short circuit. Optional wheel kits to allow a single user to move the generator around the site.

- Max output 230V 4000W.
- Max output 400V 7000W
- Rated output 230V 3600W.
- Rated output 400V 6500W.
- 230/400 output voltage (V)
- Noise level @ 7m 75dB(a)
- 6,5 litre fuel tank
- Run time up to 2,6 hours.
- Weight 88 kg.
- Dimensions: L: 755, W: 550, H: 560.

**GENTEC
ENERGY**

Slotermeer 5-5
8502 TM Joure
Netherlands
E-mail: mail@gentec-energy.com
<http://www.aggregaat.eu>
<http://www.gentec-energy.com>
Tel. +31(0)58-2883944

